



| | MM |
|--------------------------------|-----|
| A Total Width | |
| B Fixing Bracket Width | |
| C Maximum Fixing Bolt Diameter | 7.0 |
| D PCD | 324 |
| E Minimum PCD | 299 |
| F Fan blade diameter | 200 |
| G Basket diameter | 235 |
| I Basket depth | 45 |
| J Junction box protrusion | 60 |
| K Fan blade/motor protrusion | 25 |
| L Overall depth | 70 |

All measurements shown are in millimeters
 Measurements shown have manufacturing tolerances of +/- 2mm

| SPECIFICATION | | | | | |
|------------------|---------|------------------|-----------|--------------------------------|------|
| Motor | PSC | Speed (RPM) | 2500 | Bearings | Ball |
| Voltage (V) | 220/240 | Motor Protection | Th. Prot. | Weight (Kg) | 2.3 |
| Frequency (Hz) | 50/60 | Insulation Class | F | Air Volume (M ³ /h) | 760 |
| Power In/Out (W) | 67 | Protection Class | IP54 | Noise Level (dBA) | 66 |
| Current (A) | 0.24 | Temp. Range | -30 +60 | Capacitor (MF) | 1.5 |

POLE STAR
 PRODUCTS LIMITED

| POLE STAR PRODUCTS LIMITED | |
|----------------------------|-----------------------|
| Product Code | GMA1-200B-1E-1 |
| Projection | A4 |
| Angle | Scale: |
| ± 3° | Sheet: 1 of |

