



- NOTE:**
1. RUNOUT OF SHAFT SHALL NOT EXCEED 0.0015mm PER mm OF SHAFT EXTENSION.
  2. MATERIAL FOR SHAFT:- EN8, Mn PHOSPHATED, R.P. OILED BY DW917
  3. SHELL, TERMINAL COVER & R'BASE SHOULD BE BLACK POWDER COATED WITH GLOSSY POLYESTER POWDER COAT.
  4. ALL REMAINING STEEL COMP. TO BE PLATED
  5. BOTH END SHIELDS TO BE ALUMINIUM PRESSURE DIE CAST & CHEMICAL TREATED.
  6. MOTOR SHOULD COMPLY WITH RoHS NORMS.

SPECIFICATION					
Motor	Split Phase	Speed (RPM)	1425	Bearings	Ball
Voltage (V)	230/240	Motor Protection	IP42	Weight (Kg)	
Frequency (Hz)	50	Insulation Class	F	Noise dB(A)	
Power In/Out (W)	125	Protection Class	IP44		
Current (A)	1.2				

**POLE STAR**  
PRODUCTS LIMITED

POLE STAR PRODUCTS LIMITED	
Product Code	<b>60FM125R-2</b>
Projection Angle	± 3°
	A4
	Scale: Sheet: 1 of