



NOTE:

1. RUNOUT OF SHAFT SHALL NOT EXCEED 0.0015mm PER mm OF SHAFT EXTENSION.
2. MATERIAL FOR SHAFT:- EN8, Mn PHOSPHATED, R.P. OILED BY DW917
3. SHELL, TERMINAL COVER & R'BASE SHOULD BE BLACK POWDER COATED WITH GLOSSY POLYESTER POWDER COAT.
4. ALL REMAINING STEEL COMP. TO BE PLATED
5. BOTH END SHIELDS TO BE ALUMINIUM PRESSURE DIE CAST & CHEMICAL TREATED.
6. MOTOR SHOULD COMPLY WITH RoHS NORMS.

SPECIFICATION

Motor	Split Phase	Speed (RPM)	1425	Bearings	Ball
Voltage (V)	230/240	Motor Protection	Th.Prot.	Weight (Kg)	
Frequency (Hz)	50	Insulation Class	F	Noise dB(A)	
Power In/Out (W)	185	Protection Class	IP44		
Current (A)	2.1				

POLE STAR
PRODUCTS LIMITED

POLE STAR PRODUCTS LIMITED	
Product Code	60FM185R-4
Projection Angle	± 3°
	A4
	Scale:
	Sheet: 1 of