



Optimum energy Efficiency point

Input Power 1,339 Kw
Air Flow 9456 m3/h
Pressure 199 Pa
RPM 1349 RPM

	N	Abs. Pw	I	Lpa 3 m
	[RPM]	[kW]	[A]	[dB(A)]
(1)	1430	0,80	3,61	71.5
(2)	1416	1,10	4,96	71.5
(3)	1410	1,39	5,92	73.5

Air performance obtained in compliance with AMCA 210 and ISO 5801, Installation A category in VIP full nozzle and without guard grill.

Sound power levels and sound energy levels determined in accordance with ISO 3744. The uncertainty conforms to ISO 12001, accuracy grade 2.

Standard operating condition
Continuous duty - S1
International protection IP 55
Voltage and frequency range in compliance with IEC 60034-1

ERP 2015
 $\eta_{A,Stat}$ 38,9 % Efficiency grade 34,5 %

Description	Part Number	□ L0	□ L1	ØD0	ØD1	H0	H1	H2	H3	Motor Frame	Kg
UH 063-23-4M-P-0X06Y-A	1400087	730	680	634	673	363	24	102	15	90 B14	16

SPECIFICATION					
Motor	PSC	Speed (RPM)	1349	Bearings	Ball
Voltage (V)	230	Motor Protection	Th.Prot.	Weight (Kg)	16
Frequency (Hz)	50	Insulation Class		Noise dB(A)	
Power In/Out (W)	1100	Protection Class		Amb. Temp. (°C)	-15/+60
Current (A)	7.02	Capacitor (MF)	40		

POLE STAR
PRODUCTS LIMITED

POLE STAR PRODUCTS LIMITED	
Product Code	PMAHD1-630B4-1
Projection Angle	± 3°
Scale:	A4
Sheet:	1 of 1